



TOP PLATES -
with side storage slot for load lock

BOTTOM PLATES

CORNER THICKNESS



EGG ACCESS

LOAD LOCK STYLE



CORNER/CENTRE POST SIZE

CORNER/CENTRE POST THICKNESS



SLIDERS THICKNESS SP M

SHELF SPACING

CROSS BARS

CROSS BARS THICKNESS



CASTERS - Polyolefin/Polypropeline SP
Durable - water and chemical resistant
Grease nipple.
Zinc plated caster forks SP SS

	A LIGHT DUTY	B HEAVY DUTY	C ORIGINAL
TOP PLATES - with side storage slot for load lock	3 1/2" x 2"	6 3/4" X 2 1/2"	2" x 2" angle iron
BOTTOM PLATES	4 3/4" x 4 1/4"	8" x 4"	2" x 2" angle iron
CORNER THICKNESS	12 Gauge	11 Gauge	11 Gauge
EGG ACCESS	1 side	1 side	1 side
LOAD LOCK STYLE	Flat one bend	3/4" Tubing	Round posts
CORNER/CENTRE POST SIZE	1" x 2"	1" x 2"	1" x 2"
CORNER/CENTRE POST THICKNESS	16 Gauge	11 Gauge	11 Gauge
SLIDERS THICKNESS SP M	14 Gauge	14 Gauge	14 Gauge
SHELF SPACING	4"	4"	4"
CROSS BARS	None	4 Front/back	None
CROSS BARS THICKNESS	n/a	11 Gauge	n/a
CASTERS - Polyolefin/Polypropeline SP Durable - water and chemical resistant Grease nipple. Zinc plated caster forks SP SS	Standard**	SS axle/rod	SS axle/rod

✓ **FINISH** : Pre-galvanized & Hot Dip Galvanized M

✓ **CONSTRUCTION**: Welded, Bolted & Riveted M

SP Available as a spare part

M Nuts/Bolts & Rivets allow for easy maintenance
of parts which may require repairs

SS Stainless steel available

